



Rail Lift

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

4,000 - 6,000 LBS. CAPACITIES

Available Options

- Upper Travel Limit Switch
- In Motor Warning Beeper and Flashing Light on a Post X 60" High or Wall Mounted on Bracket
- Interlocking Gate
- Aluminum Bridges
- Larger Steel Bridges
- Power Pack Covers
- Other _____

Design Highlights

- Low Profile for Surface-mounted Applications
- No Pit Construction Required
- Three-sided Platform
- Heavy-duty I-beam Deck Understructure
- Excellent End-load Stability in Fully Raised Position
- Displacement style Cylinder with Internal Stops
- Self-contained Power Unit/control Panel
- Standard Pre-wired Control Panel
- NEMA 4X Push-button Controller with 15' Cord
- Superior Speed-to-horsepower Ratio Compared to Scissor-style Dock Lifts
- Direct thrust Cylinders Provide Constant Speed Through Full Range of Travel
- Checker Plate or Smooth Deck Surface
- Sealed Guide Bearing Rollers
- Fused 24-volt Control Circuit

Project Information

Job Name _____

Address _____

General Contractor _____

Distributor _____

Model _____ Quantity _____ Voltage/Phase _____



Rail Lift

LOADWARRIOR® SERIES

LIFT PRODUCTS SPECIFICATIONS

4,000 - 6,000 LBS. CAPACITIES

Model No.	Lift Capacity [lbs.]	Deck Size [in]	Feet Per Minute [FPM]	HP	Ship. Weight [lb]
SRL45-4	4,000	48 x 60	9	5	2,050
SRL46-4	4,000	48 x 72	9	5	2,200
SRL55-4	4,000	60 x 60	9	5	2,150
SRL56-4	4,000	60 x 72	9	5	2,500
SRL57-4	4,000	60 x 84	9	5	2,650
SRL58-4	4,000	60 x 96	9	5	2,800
SRL66-4	4,000	72 x 72	9	5	2,800
SRL67-4	4,000	72 x 84	9	5	2,950
SRL68-4	4,000	72 x 96	9	5	3,100
SRL610-4	4,000	72 x 120	9	5	3,300
SRL612-4	4,000	72 x 144	9	5	3,600
SRL45-6	6,000	48 x 60	7	5	2,200
SRL46-6	6,000	48 x 72	7	5	2,400
SRL55-6	6,000	60 x 60	7	5	2,400
SRL56-6	6,000	60 x 72	7	5	2,750
SRL57-6	6,000	60 x 84	7	5	2,875
SRL58-6	6,000	60 x 96	7	5	3,000
SRL66-6	6,000	72 x 72	7	5	3,100
SRL67-6	6,000	72 x 84	7	5	3,250
SRL68-6	6,000	72 x 96	7	5	3,400
SRL610-6	6,000	72 x 120	7	5	3,700
SRL612-6	6,000	72 x 144	7	5	3,900

